



# Learnings from the Australian Mining Industry applied to development of In-Situ Resource Utilisation systems for Mars.

Timothy M Pelech




Photo: Century Mine, wikimedia commons

# The Problem


*Low confidence data, technology and models are used to support the hypothesis that ISRU on Mars will enable the first human mission.*

## LHD v Load and Haul Operational Assumptions:

- Distance to ore body:** [50:2000] m
- Distance to Waste dump:** 100m average
- Haulage Speed:** 0.8 m/s (+/- 50%)
- Excavation Speed Excavator:** 0.25 m<sup>3</sup>/h (+/- 30%)
- Excavation Speed LHD:** 0.27 m<sup>3</sup>/h (+/- 20%)
- Average Payload LHD:** 60kg LHD, 100kg truck (+/-20%)
- Average Payload Hauler:** 100kg truck (+/-20%)
- H<sub>2</sub>O Grade:** 9% (+/- 50%)
- Recovery:** 60% (+/- 20%)
- Hauler Mass:** 8kg (+50%)
- LHD Mass:** 8kg (+50%)
- Hauler Mass:** 8kg (+50%)
- Daily Operating Hours:** 6 (+/- 40%)




# Terrestrial Industry Analogies - Grade Control and Selectivity



20 m


- **Expected geology (uncertain)**

F1 = 4000 t, 10%  
F2 = 4000 t, 10%  
F3 = 7000 t, 8%  
F4 = 8000 t, 8%  
F5 = 6000 t, 12%  
Total ore = 29000 t, 9.3%  
Waste = 15000 t



- **Actual geology**


F1 = 4000 t, 10%  
F2 = 5000 t, 8%  
F3 = 3000 t, 3%  
F4 = 6000 t, 10%  
F5 = 5000 t, 11%  
F6 = 5000 t, 12%  
Total ore = 28000 t, 9.0%  
Waste = 8000 t




# Mars Operational Hypothesis






- Curiosity DAN data shows variability in location and depth. (Litvak et al, 2014)
- Risk of not achieving product targets (15 t H<sub>2</sub>O for return mission) (Abbud-Madrid et al, 2016).
- Testing of areas for quality of ore before mining leads to improvements in the process.
  - High grade = Less material moved, for more product.
  - High grade = Less processing and mining equipment required for more product.
  - High grade = less thermal power required for processing.
- Selectivity in mining increases average grade and output in a mill constrained system.





# Terrestrial Industry Analogies – Efficient Excavation Setup




- Excavator productivity depends heavily on operator ability and setup.
- Setting up faces.
- Loading efficiency.
- Utilising gravity to propagate failure planes in rock.




# Horizontal excavation – necessary but inefficient



# Pulling up – utilising gravity to propagate failure planes






- 10-20% productivity gain compared to drop cut.





# Horizontal “Drop Cut” to establish faces








# Mars Operational Hypothesis – Particle Size and Recovery




- Finer fragmented particles from excavation will lead to higher recovery from ore.
- From resource to product, the entire system must be considered as one to obtain maximum productivity. Not separate components.






$$\begin{aligned} \text{Surface Area} &= 4\pi r^2 \\ \text{Exposed H}_2\text{O molecules} &\propto \text{Surface Area} \\ \therefore \text{Water Recovery} &\propto \text{Surface Area} \end{aligned}$$

# Terrestrial Industry Analogies – Infrastructure and Systems development




- Time and energy is required to properly establish a mine.
- Mine capital development.
- Processing plant
- Other
- Eg. Communications
  - UG communication and navigation
  - Significant effect on safety and productivity.




# Mars Operational Hypothesis – Communications and Navigation




- Communications and navigation systems will need to be established in a similar fashion for robotic mining equipment on Mars.
- This success of this system will have a significant impact on the productivity of the mine.




# Mars Operational Hypothesis – Site Establishment




- Deployment of equipment
- Time Required to establish mining front.
- Establish haul route network.
- Time delay to first ore in process plant.




High human input period.




# Terrestrial Industry Analogies – Waste Management




- Waste movement is the largest mining cost component for open pit operations.
- All material moved swells 30% volume after excavation.
- Open pit operations use paddock dumping initially to establish a tiered dump and tip-head. Ancillary equipment (dozer) is necessary to construct a tiered dump.



# Mars Operational Hypothesis



- More than 50% of all material volume moved will be tailings or waste.
- Footprint of waste dump depends on size of hauler tub.
- Dumping location to be controlled by navigation system.
- Efficient use of waste dumps is important.






# Conclusion

**Problem:** *Low confidence data, technology and models are used to support the hypothesis that ISRU can be used on Mars for the first human mission.*

**Solution:**

1. Leverage terrestrial mine planning techniques and analysis as a tool.
2. Develop a Mars ISRU system using mining system for operational testing.
3. Demonstrate system in geological analogue environment to increase knowledge.



Questions?

# References

Abbud-Madrid, A, Beaty, D W, Boucher, D, Bussey, B, Davis, R, Gertsch, L, Hays, L E, Kleinhenz, J, Meyer, M A, Moats, M, Mueller, R P, Paz, A, Suzuki, N, Susante, P V, Whetsel, C and Zbinden, E A, 2016. Report of the Mars Water In-Situ Resource Utilization (ISRU) Planning (M-WIP) Study, California Institute of Technology.

Clarke, J, Wilson, D and Keeling, J, 2016. Moon Plain South Australia: a testing ground for Martian resource extraction?, *MESA Journal*, 81:66-68.

Dickson, D, Sibille, L, Galloway, G, Mueller, R, Smith, J, Mantovani, J, and Schreiner, S, 2016. Modelling Dynamics of Counter-Rotating Bucket Drum Excavation for In-Situ Resource Utilization (ISRU) in Low-Gravity Environments, *Proceedings in 15th Biennial ASCE Conference on Engineering, Science, Construction, and Operations in Challenging Environments*, Orlando, Florida, April 11–15 2016.

Litvak, M, Mitrofanov, I, Lisov, D, Behar, D, Boynton, W, Deflores, L, Fedosov, F, Golovin, D, Hardgrove, C, Harshman, K, Jun, I, Kozyrev, A, Kuzmin, R, Malakhov, A, Milliken, R, Mishna, M, Moersch, J, Mokrousov, M, Nikiforov, S, Shvetsov, V, Stack, K, Starr, R, Tate, C, Tretyakov, V, Vostrukhin, A and the MSL Team, 2014. Local variations of bulk hydrogen and chlorine-equivalent neutron absorption content measured at the contact between the Sheepbed and Gillespie Lake units in Yellowknife Bay, Gale Crater, using the DAN instrument onboard Curiosity, *Journal of Geophysical Research: Planets*, 119:1259-1275.

López-Delgado, A, López-Andrés, S, Padilla, I, Alvarez, M, Galindo, R and Vázquez, A, 2014. Dehydration of Gypsum Rock by Solar Energy: Preliminary Study, *Geomaterials*, 4:82-91.

Skonieczny, K, Wettergreen, D and Whittaker, W, 2016. Advantages of continuous excavation in lightweight planetary robotic operations, *The International Journal of Robotics Research*, 35(9):1121–1139.

Zacny, K, Chu, P, Paulsen, G, Avanesyan, A, Craft, J, and Osborne, L 2012. Mobile In-Situ Water Extractor (MISWE) for Mars, Moon and Asteroids In-Situ Resource Utilization, *Proceedings in AIAA SPACE 2012 Conference & Exposition*, Pasadena, California, 11 - 13 September 2012.